



SPACE DETONATING TRANSFER LINE (DTL)

Pyroalliance designs Detonating Transfer Lines made of different materials, sizes, shapes and cladding. Those are used to transmit a pyrotechnic order from one point to another, allowing a function to be triggered (separate, neutralize or ignite).

Among these different Detonating Transfer Lines, some operate in a deflagration mode, whereas others operate in a detonating mode. This is the case of the Detonating Transfer Line described hereafter.

These Detonating Transfer Lines, combined with other Pyroalliance's products, are part of Separation, Flight Termination or Ignition pyro-chains. They are designed and manufactured under Pyroalliance design authority.

Detonating Transfer Line (DTL)

Operation mode

Detonating transfer lines are designed to transfer a detonation from one point to another.

A line consists in a lead-free Mild Detonating Cord (MDC) jacketed and covered by a fiberglass braiding. Each end is equipped with a booster relay, joints and protection for sealing.

The end tips can be from different types (short or long, flexible or rigid) and adapted to the system or manifold it will be connected to.

Benefits

- Hermetic after operation
- No external effect when interfaced
- High velocity
- High reliability and safety

Application

Space launcher pyrotechnic chains



Pyroalliance's DTL equips the Vega family- ESA

Key figures

Detonation velocity (Typical value): 6800 m/s

Cladding: Glass fibre braiding

Operating temperature: Down to -80°C Up to + 100°C

For more information please contact us. Visit our website: www.pyroalliance.com

Product Classification

- Number UN: UN0384
- Storage class: 1.4S
- Not restricted by ITAR regulation

Les Mureaux Plant - Headquarters

139, Route de Verneuil - BP 2052 78132 Les Mureaux cedex – France Tel. +33 (0)1 34 92 44 44 – Fax +33 (0)4 94 22 86 99

Produced by the Communication Department of Pyroalliance

Photo credits: Pyroalliance and ESA