



SPACE MANIFOLD 1xN

Pyroalliance designs and manufactures high reliability manifolds for space applications, distributing a pyrotechnical signal from one end to the others (1xN).

This standard equipment meets the European launcher programs requirements, with associated justification level, and is not restricted by ITAR regulations.

These manifolds, combined with other Pyroalliance's products, are part of Separation, Flight Termination or Ignition pyro-chains. They are designed and manufactured under Pyroalliance design authority.

Manifold

The function of the manifold is to transmit a detonating signal from generally one or a few inputs to several output transfer lines (demultiplexer).

Our current product line offers up to 9 outputs for 1 input. Other versions are available on request.

Those manifolds are made of aluminium alloy housing. Organized in a pyrotechnic chain, they allow operating multiple terminal functions from one single initial electrical order.

Operation mode

When receiving an input “signal”, the manifold propagates, within a few microseconds, a signal to each output.

This component is interfaced with detonating transfer lines.

Benefits

- Integrated function for cost efficiency
- Light and compact
- Without any external effects
- Reach compliant
- High reliability/safety

Applications

Pyrotechnic transfer lines interconnection

[For more information please contact us.](#)
[Visit our website: www.pyroalliance.com](http://www.pyroalliance.com)



Pyroalliance's Manifold flies on Vega - ESA

Key figures

Number of channels (In & Out):	3 to 10
High synchronicity (Typical values):	< 20 μ s between input initiation to the output ends
Leak rate:	< 10^{-3} atm.cm ³ / sec
Operating temperature:	Down to -80°C Up to + 100°C
Storage temperature:	-10°C to +40°C
Humidity Rate (HR):	<60%

Product Classification

- Number UN: UN0432
- Storage class: 1.4S
- Not restricted by ITAR regulation

Les Mureaux Plant - Headquarters

139, Route de Verneuil - BP 2052
78132 Les Mureaux cedex – France
Tel. +33 (0)1 34 92 44 44 – Fax +33 (0)4 94 22 86 99

Produced by the Communication Department of Pyroalliance

Photo credits: Pyroalliance and ESA

This document is not contractual and it is the property of Pyroalliance. It is not able to be announced to thirds and/or reproduced without prior approval written of Pyroalliance and its contents are not able to be revealed. – © Pyroalliance 2019