



## SPACE

### M10 SEPARATION NUT P/N ME0038AA

Pyroalliance designs a wide range of separation nuts, used for the in orbit deployment of antenna reflectors and solar generators on satellites or used for the separation of satellites of a constellation, assembled on a dispenser.

With a recorded rate of in-flight success of 100% over more than 10000 separation nuts delivered until today to its customers, Pyroalliance provides with such separation nuts extremely reliable solutions of Hold down and release.

More generally, Pyroalliance delivers complete pyrotechnic chains adapted to its customers' needs. They are designed and manufactured under Pyroalliance design authority.

# SEPARATION NUT

## Operating mode

The separation nut is a pyro-mechanism which performs two functions:

1. maintaining a pre-loaded assembly of two set,
2. releasing the assembly upon an electrical order.

The energy required to achieve the release is provided by gas pressure (pyrotechnic gas generated by the initiator).

## Benefits

- **Reliability**  
High reliability of the product is granted by the implementation of redundant initiators and the systematic in-factory functional testing (100%) of the mechanical part by cold gas actuation (instead of pyrotechnic gas) and reseted after test.
- **Actuation time and synchronicity**  
By nature, pyrotechnic actuators allow a very low actuation time and associated to a low standard deviation. Consequently high level of synchronicity is granted for several nuts activated simultaneously, as this is the case for holding satellites on dispensers.

## Applications

- Satellite release from a dispenser

## Typical performances and features

Operation time (Typical values):	Few ms
Over all dimensions* (Width/Depth/Height):	56mm / 41mm / 53mm
Bolt dimensions:	M10 x 1.25
Weight:	190 g
Operating temperature:	-60°C to +80°C
Operating bolt tensions:	Up to 20kN

*\*Dimensions without initiators*

*\*\*NASA Standard Initiators*



*Pyroalliance's equipment on board Rosetta Great Gain Antenna - ESA*

## Classification Product

- Number UN: UN0173
- Storage class: 1.4S
- Not restricted by ITAR regulation

## For more information

Contact us: [customer-info@pyroalliance.com](mailto:customer-info@pyroalliance.com)

**Les Mureaux Plant - Headquarters**  
139, Route de Verneuil - BP 2052  
78132 Les Mureaux cedex – France  
Tel. +33 (0)1 34 92 44 44

[www.pyroalliance.com](http://www.pyroalliance.com)

Follow us on [LinkedIn](https://www.linkedin.com/company/pyroalliance)

